

2010 NSMMS Abstract Submission

Due Date: 21 December 2009

Notifications of selection results will be emailed by 31 January 2009

Abstract Title: MSFC Thermal Protection System Materials on MISSE-6

Full Name: Miria Fincknor

**Company/
Affiliation:** NASA/MSFC

Phone: 256-544-9244 **Email:** miria.fincknor@nasa.gov **Fax:** 256-544-0212

Abstract best fits in (check all that apply): ☐ Breakthrough Innovations ☐ Missiles & Missile Defense ☒ MISSE
☐ Space Exploration ☐ Orbital Technologies & Operations ☐ Hypersonic & Responsive Operations

Please consider my abstract for (check all that apply): ☒ Oral Presentation ☐ General Poster Session ☐ SBIR Poster Session ☐ Student Poster Session

What Classification is Your Presentation? Unclassified

What Distribution Level is Your Presentation? Unlimited

Degree(s) held by Lead Author: B.S. Materials Engineering

Where degree(s) was received: Virginia Polytechnic Institute

Current Position: Senior Materials Engineer

Co-Authors (Include Full Name and Company/Organization):

Peter Valentine NASA/MSFC

Michael Gubert US Army

Abstract:

The Lightweight Nonmetallic Thermal Protection Materials Technology (LNTPMT) program studied a number of ceramic matrix composites, ablator materials, and tile materials for durability in simulated space environment. Materials that indicated low atomic oxygen reactivity and negligible change in thermo-optical properties in ground testing were selected to fly on the Materials on International Space Station Experiment (MISSE)-6. These samples were exposed for 17 months to the low Earth orbit environment on both the ram and wake sides of MISSE-6B. Thermo-optical properties are discussed, along with any changes in mass.

**List Special
Presentation
Requirements:**

Please email the completed abstract submission form to:
Ms. Nancy Johnson, Nancy_johnson@gdit.com, 937-476-2156.
For complete information on this event visit www.usasymposium.com.



Thermal Protection System Materials on MISSE-6

Miria M. Finckenor and Peter G. Valentine
Materials & Processes Laboratory
NASA/Marshall Space Flight Center

Michael K. Gubert
US Army / Redstone Arsenal

National Space and Missile Materials Symposium
June 2010



- Acknowledgements

- Julie Henkener, system manager, Rajib Dasgupta, previous system manager, and Dr. John Alred, deputy system manager for ISS M&P
- Dr. Gary Pippin, Boeing Research & Technology, for estimated environmental exposures.
- Bill Kinard, MISSE chief scientist (retired), Karen Gibson, Ray Seals, and Sandie Gibbs, LaRC
- Beth Cook and Twila Schneider, Advanced Materials for Exploration program
- The various government and industry suppliers of the materials tested in the LNTPMT and MISSE-6 projects.
- Gerald Russell of the Aviation and Missile Research, Development, and Engineering Center (AMRDEC)




Presentation Outline

- Atomic oxygen studies as part of Lightweight Nonmetallic Thermal Protection Materials Technology Project
- Selection of LNTPMT materials for MISSE-6
- Additional material from Marshall
- Optical Property Measurements
- Discussion



Lightweight Nonmetallic Thermal Protection Materials Technology Project

- Multi-center effort (MSFC, ARC, GRC, LaRC) which also included industry
- Increase in TRL for thermal protection
- Optimize heatshields for direct entry, aerobraking or aerocapture missions
- Due to changing priorities at NASA, was only funded for first year of planned four-year project





Lightweight Nonmetallic Thermal Protection Materials Technology Project



- Environmental testing of ceramic matrix composites, ablator materials, and tile materials
 - Atomic oxygen
 - Radiation
 - Meteoroid/orbital debris impact
- Arcjet testing at ARC and AEDC – was to have occurred in second year of project
- Laser Hardened Materials Evaluation Laboratory (LHMEL) Testing at Wright-Patterson Air Force Base



Lightweight Nonmetallic Thermal Protection Materials Technology Project – AO Testing

Samples exposed to $\sim 2 \times 10^{20}$
atoms/cm² 5 eV atomic oxygen

Comparable fluence to wake
side of MISSE-6






Material Class	Manufacturer --- TPS Material
Lightweight Ablatives	NASA-ARC / Fiber Materials Inc. (FMI) --- PICA-15 NASA-ARC --- SIRCA 15F ATK Thiokol --- MX4926 Low Density Carbon Phenolic Boeing Company --- BLA-20 ITT Industries --- Acusil II International Paint --- Chartek Minteq International Inc. --- RX2390 Raytheon Missile Systems --- Hotblox Raytheon Missile Systems --- Hotblox Lite
Rigid Reusable Ceramic Tiles	NASA-ARC / Boeing Company --- AETB-12 w/TUFI and RCG NASA-ARC / Boeing Company --- BRI-20 w/HETC and RCG
Ceramic Matrix Composites (CMC's) and C-C	ATK Thiokol --- RTV-impregnated C-C C-C Adv. Technologies (C-CAT) --- ACC-6 with SiC coating GE Energy CCP --- C/SiC with MCM700 coating Hyper-Therm HTC --- Hybrid C-SiC/SiC sandwich panel MER Corp. --- C-C with SiC-HfC coating Physical Sciences, Inc. (PSI) --- HyBase D C-C with SiC coating
Ballute Thin Film Materials	Dropped from LNTPMT Phase I Effort Materials from Ball Aerospace, L'Garde, and Nexolve flown




Significant mass loss of RTV- impregnated C-C observed during ground testing led to elimination as a candidate material for MISSE-6.

Ames flew a separate set of candidate TPS materials.

Lockheed-Martin also flew a set of superlightweight ablator candidate TPS materials



MISSE-6B Wake / Ram



Ram



Wake



MISSE-6 Environmental Exposure

Ram-facing side


- $\sim 2 \times 10^{21}$ atoms/cm² atomic oxygen
- $\sim 2,600$ equivalent sun-hours UV

Wake-facing side


- $\sim 1.4 \times 10^{20}$ atoms/cm² atomic oxygen
- $\sim 1,950$ equivalent sun-hours UV

>8,400 thermal cycles of +40/-40 °C


ACC-6




PSI SiC C-C




MER SiC / HfC C-C




GE SiC / HfC




Hypertherm SiC - SiC



Hotblox Ablator



Hotblox Lite Ablator






Atomic oxygen stimulated fluorescence


- LDEF experiment A0034 showed that AO can change fluorescence of materials
- Both ram and wake Hotblox Lite more reflective in UV wavelengths, proportional to AO exposure
- Concurs with post-flight fluorescence under black light




Hotblox Ultralite Ablator



BRI-20 / HETC / RCG Tile



AETB-12 / TUFI / RCG Tile






Additional material from Marshall

- NOAX-D (non-oxide adhesive experimental) from Andy Hodge





NOAX-D	Solar Absorptance	Infrared Emittance
Pre-flight	0.855	0.86
Post-flight Ram	0.882	0.84
Post-flight Wake	0.871	0.86



Mass Changes

- Slight increase in mass for plain Hotblox, PSI SiC C-C
- No significant change in mass
 - Tile materials
 - Hotblox Lite
 - Hyper-Therm SiC – SiC
 - NOAX-D
- Slight decrease in mass
 - Hotblox Ultralite
 - C-CAT ACC-6
- Significant AO erosion of SiC / HfC materials



In conclusion:

MISSE-6 contributed to advancing the TRL of these materials.
Synergistic effects between AO, UV, and vacuum not easy to reproduce on the ground.

Further details of the LNTPMT program can be found –

- MSFC-RPT-3493: TPS Materials Properties Testing and Evaluation ---Integrated Test Plan and Report
- MSFC-RPT-3486: Effects of Space and Planetary Environments on TPS Materials --- Integrated Test Report